



Earthing Copper Barrier Tape copper tape conductive adhesive 25x3mm

Our Product Introduction

Basic Information

- Place of Origin: china
- Brand Name: jinshunlai
- Certification: IOS
- Model Number: 0.1mm-900mm
- Minimum Order Quantity: 1kg
- Price: contact us
- Delivery Time: 5day
- Payment Terms: L/C, T/T , Western Union,D/P
- Supply Ability: 90000ton



Product Specification

- Adhesion: 3.5N/cm
- Adhesive: Acrylic
- Application: Electrical Insulation
- Surface Resistance: 0.02Ω
- Tensile Strength: 25N/cm
- Width: 50mm
- Highlight: **Earthing copper barrier tape,
25x3mm copper barrier tape,
25x3mm copper tape conductive adhesive**



More Images



for more products please visit us on copper-solid.com

Product Description

Key attributes

Industry-specific attributes

Material	Copper Foil
Cu (Min)	99.97%
Alloy Or Not	Non-Alloy

Other attributes

Place of Origin	Shandong, China
Application	Electronic
Width	30-1000mm
Grade	Copper Foil
Model Number	C1020,C1100,C1220
Brand Name	Shengming
Processing Service	Bending, Welding, Decoiling, Cutting, Punching
Product Name	Copper Foil 0.1mm
Keyword	Manufacturer Copper Coil
MOQ	20kg
Color	Red Coppery
Surface	Bright
Standard	ASTM JIS GB
PAYMENT TERM	30%TT+70% Balance
Thickness	0.1-3.0mm
Type	coil/ strip
DELIVERY TIME	7-15 Days

Packaging & delivery

Package Type:	Export standard packing or according to customers's requirement <input type="text"/>
---------------	--

Supply Ability

Supply Ability	1000 Ton/Tons per Week
----------------	------------------------

Product Description

Type	strip,tape,band,coil,roll
Standard	ASTM B194 ASTM B569 JIS H3130 JIS3100 JIS3110 GB/T 2059 GB/T 2061
Material	C10100,C10200,C10300,C10400,C10500,C10700,C10800,C10910,C10920,C10930,C11000,C11300,C11400,C11500,C11600,C12000,C12200,C12300,C12500,C14200,C14420,C14500,C14510,C14520,C14530,C17200,C19200,C21000,C23000,C26000,C27000,C27400,C28000,C33000,C33200,C37000,C44300,C44400,C44500,C60800,C63020,C65500,C68700,C70400,C70620,C71000,C71500,C71520,C71640,C72200,etc
Width	30-1000mm
Thickness	0.1-3.0mm
Hardness	1/4 hard, 1/2hard,full hard,soft,etc.
Surface	mill,polished,film-coated
Export to	Singapore,Indonesia,Ukraine,Korea,Thailand,Viet Nam,Saudi Arabia,Brazil,Spain,Canada,USA,Kuwait,Dubai,Oman,Kuwait,Peru,Mexico,Iraq,Russia,Malaysia,etc
Package	Standard export package or as required.
DELIVERY TIME	7-15 Days

copper foil:

It has a strong wear resistance. It has high strength, strong hardness and chemical resistance. It also has prominent machining

mechanical performance.

It can be made for a variety of deep-drawn and bending force components, such as pins, rivets, washers, nuts, ducts, barometers,

screens, radiator parts.

It has good mechanical properties, good plasticity in hot state, the cold plastic is acceptable, good machinability, easy welding

and welding, corrosion, is a widely used material.



Wuxi Jinnuo copper Co.,Ltd



+86-17763564398



sales01@shuangheyisteel.com



copper-solid.com

32 Chengnan Road, New District, Wuxi City, Jiangsu Province, China